




## FV 15 / 3100

| Type                | FV 15 / 3100        | Overall Dimensions                                                                                                                                                         | ( mm )  |
|---------------------|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| Size                | E0                  | A                                                                                                                                                                          | 560     |
| Centrifugal Force   | 3049 kgF / 29,91 kN | B                                                                                                                                                                          | 260     |
| Statical Moment     | 1210 kgmm           | C                                                                                                                                                                          | 271     |
| Phase               | 3                   | D                                                                                                                                                                          | 155     |
| Voltage             | 400 V               | E                                                                                                                                                                          | 225     |
| Frequency           | 50 Hz               | G                                                                                                                                                                          | 4 X M20 |
| Power               | 2 kW                | F                                                                                                                                                                          | 68      |
| Rpm.                | 1500 d/d            | M                                                                                                                                                                          | 204     |
| Current             | 3,50 A              | N                                                                                                                                                                          | 244     |
| Efficiency          | 80%                 | <br><br>Made in TÜRKİYE<br>Femaş Elektrik Motor San.ve Tic. Ltd.Şti.<br>fvm@fvm.com.tr |         |
| Serv.               | S1                  |                                                                                                                                                                            |         |
| Ambient Temperature | 40°C                |                                                                                                                                                                            |         |
| Safety Class        | IP 66               |                                                                                                                                                                            |         |
| Insulation Class    | F                   |                                                                                                                                                                            |         |
| Unit Weight         | 85 kg               |                                                                                                                                                                            |         |
| Bearing Type        | NJ 2309 C4          |                                                                                                                                                                            |         |
| Cable Gland         | M25 X 1,5           |                                                                                                                                                                            |         |

